

COMPRESSED AIR FILTER ELEMENTS

COMPATIBLE FOR FRIULAIR (2)

ORIGINAL MODEL NUMBER	AFE MODEL NUMBER GRADE P (P)	AFE MODEL NUMBER GRADE U (S)	AFE MODEL NUMBER GRADE H (X)	AFE MODEL NUMBER GRADE S	AFE MODEL NUMBER GRADE C (Z)
T* 008	EFAT008P-NAAE	EFAT008U-WAAE	EFAT008H-WAAE	-	EFAT008C-NAAE
T* 012	EFAT012P-NAAE	EFAT012U-WAAE	EFAT012H-WAAE	-	EFAT012C-NAAE
T* 018	EFAT018P-NAAE	EFAT018U-WAAE	EFAT018H-WAAE	-	EFAT018C-NAAE
T* 030	EFAT030P-NAAE	EFAT030U-WAAE	EFAT030H-WAAE	-	EFAT030C-NAAE
T* 052	EFAT055P-NAAE	EFAT055U-WAAE	EFAT055H-WAAE	-	EFAT055C-NAAE
T* 080	EFAT080P-NAAE	EFAT080U-WAAE	EFAT080H-WAAE	-	EFAT080C-NAAE
T* 120	EFAT120P-NAAE	EFAT120U-WAAE	EFAT120H-WAAE	-	EFAT120C-NAAE
T* 160	EFAT160P-NAAE	EFAT160U-WAAE	EFAT160H-WAAE	-	EFAT160C-NAAE
T* 220	EFAT220P-NAAE	EFAT220U-WAAE	EFAT220H-WAAE	-	EFAT220C-NAAE
T* 250	EFAT250P-NAAE	EFAT250U-WAAE	EFAT250H-WAAE	-	EFAT250C-NAAE
T* 400	EFAT400P-NAAE	EFAT400U-WAAE	EFAT400H-WAAE	-	EFAT400C-NAAE

AFE Filtration Grade	P	U	H	S	C
Compatible To Friulair (2) Filtration Grade	P	S	X	-	Z
Particle Removal Down To	3 micron	1.0 micron	0.01 micron	-	N/A
Oil Removal Down To	N/A	0.1 mg/m ³	0.01 mg/m ³	-	0.003 mg/m ³
End Caps Material	Aluminium	Aluminium	Aluminium	-	Aluminium
Filtration Material	Pleated Cellulose Media	Pleated Borosilicate Media	Pleated Borosilicate Media	-	Pleated Carbon Media
O-Ring Material	Nitrile	Nitrile	Nitrile	-	Nitrile
Sleeve / Support Material	Stainless Steel	Stainless Steel	Stainless Steel	-	Stainless Steel
Maximum Operating Temperature	80°C (176°F)	80°C (176°F)	80°C (176°F)	-	60°C (140°F)
Drainage Layer	None	Needle Felt	Needle Felt	-	None



Airfilter Engineering reserves the right to change specifications and details without prior notice. The brand name mentioned above is for identification purpose only and may be registered trade mark of respective its owner. Airfilter Engineering disclaims any and all right to this trademark. (Rev 0. 190115)

AIRFILTER[®]
ENGINEERING

www.airfilterengineering.com