

# COMPRESSED AIR FILTER ELEMENTS

## COMPATIBLE FOR SULLAIR (1)

ORIGINAL MODEL NUMBER	AFE MODEL NUMBER GRADE U (PF)	ORIGINAL MODEL NUMBER	AFE MODEL NUMBER GRADE H (PA)	ORIGINAL MODEL NUMBER	AFE MODEL NUMBER GRADE SC / C (PC)
2500024-423	ESA0020U-FAAE	2500024-431	ESA0020H-FAAE	2500024-443	ESA0013SC-NAAE
2500024-424	ESA0035U-FAPE	2500024-432	ESA0035H-FAPE	2500024-444	ESA0027SC-NAAE
2500024-425	ESA0065U-FAPE	2500024-433	ESA0065H-FAPE	2500024-445	ESA0053SC-NAAE
2500024-426	ESA0125U-FAPE	2500024-434	ESA0125H-FAPE	2500024-446	ESA0084SC-NAAE
-	-	-	-	2500024-447	ESA0140SC-NAAE
2500024-427	ESA0170U-FAPE	2500024-435	ESA0170H-FAPE	2500024-448	ESA0180SC-NAPE
2500024-428	ESA0420U-FAPE	2500024-436	ESA0420H-FAPE	2500024-439	ESA0420C-NAPE
2500024-429	ESA0700U-FAPE	2500024-437	ESA0700H-FAPE	2500024-440	ESA0700C-NAPE
2500030-644	ESA0850U-FAPE	2500030-655	ESA0850H-FAPE	2500030-646	ESA0850C-NAPE
2500024-430	ESA1315U-FAPE	2500024-438	ESA1315H-FAPE	2500024-441	ESA1315C-NAPE

AFE Filtration Grade	P	U	H	S	C
Compatible To Sullair (1) Filtration Grade	U	-	PA	-	PC
Particle Removal Down To	3 micron	-	0.01 micron	-	N/A
Oil Removal Down To	N/A	-	0.01 mg/m <sup>3</sup>	-	0.003 mg/m <sup>3</sup>
End Caps Material	Plastic	-	Plastic	-	Plastic
Filtration Material	Pleated Cellulose Media	-	Pleated Borosilicate Media	-	Pleated Carbon Media
O-Ring Material	Nitrile	-	Nitrile	-	Nitrile
Sleeve / Support Material	Stainless Steel	-	Stainless Steel	-	Stainless Steel
Maximum Operating Temperature	80°C (176°F)	-	60°C (176°F)	-	60°C (140°F)
Drainage Layer	None	-	Foam	-	None



Airfilter Engineering reserves the right to change specifications and details without prior notice. The brand name mentioned above is for identification purpose only and may be registered trade mark of respective its owner. Airfilter Engineering disclaims any and all right to this trademark. (Rev 0. 190115)

**AIRFILTER<sup>®</sup>**  
**ENGINEERING**

[www.airfilterengineering.com](http://www.airfilterengineering.com)