


# COMPRESSED AIR FILTER ELEMENTS

## COMPATIBLE FOR SULLAIR (2)

ORIGINAL MODEL NUMBER	AFE MODEL NUMBER GRADE P	AFE MODEL NUMBER GRADE U (SCF SCR PF PR)	AFE MODEL NUMBER GRADE H (SCH SCHR PH)	AFE MODEL NUMBER GRADE S	AFE MODEL NUMBER GRADE C (SCC PC)
*20	-	ESAE20020U-WAPE	ESAE20020H-WAPE	-	ESAE20020C-WAPE
*40	-	ESAE20040U-WAPE	ESAE20040H-WAPE	-	ESAE20040C-WAPE
*65	-	ESAE20065U-WAPE	ESAE20065H-WAPE	-	ESAE20065C-WAPE
*125	-	ESAE20125U-WAPE	ESAE20125H-WAPE	-	ESAE20125C-WAPE
*235	-	ESAE20235U-WAPE	ESAE20235H-WAPE	-	ESAE20235C-WAPE
*340	-	ESAE20340U-WAPE	ESAE20340H-WAPE	-	ESAE20340C-WAPE
*465	-	ESAE20465U-WAPE	ESAE20465H-WAPE	-	ESAE20465C-WAPE
*700	-	ESAE20700U-WAPE	ESAE20700H-WAPE	-	ESAE20700C-WAPE
*910	-	ESAE20910U-WAPE	ESAE20910H-WAPE	-	ESAE20910C-WAPE
*1315	-	ESAE21315U-WAPE	ESAE21315H-WAPE	-	ESAE21315C-WAPE
*2120	-	ESAE22120U-WAAE	ESAE22120H-WAAE	-	ESAE22120C-WAAE

AFE Filtration Grade	P	U	H	S	C
Compatible To Sullair (2) Filtration Grade	-	SCF, SCR, PF, PR	SCF, SCHR, PH	-	SCC, PC
Particle Removal Down To	-	1.0 micron	0.01 micron	-	N/A
Oil Removal Down To	-	0.1 mg/m <sup>3</sup>	0.01 mg/m <sup>3</sup>	-	0.003 mg/m <sup>3</sup>
End Caps Material	-	Plastic	Plastic	-	Plastic
Filtration Material	-	Pleated Borosilicate Media	Pleated Borosilicate Media	-	Pleated Carbon Media
O-Ring Material	-	Nitrile	Nitrile	-	Nitrile
Sleeve / Support Material	-	Stainless Steel	Stainless Steel	-	Stainless Steel
Maximum Operating Temperature	-	80°C (176°F)	80°C (176°F)	-	60°C (140°F)
Drainage Layer	-	Needle Felt	Needle Felt	-	None



Airfilter Engineering reserves the right to change specifications and details without prior notice. The brand name mentioned above is for identification purpose only and may be registered trade mark of respective its owner. Airfilter Engineering disclaims any and all right to this trademark. (Rev 0. 190115)



[www.airfilterengineering.com](http://www.airfilterengineering.com)